

**Q: What are the differences between SV218 Series and SV198 Series?**

	SV218 Series	SV198 Series
Power Rating	120V/60Hz (USA & Canada Standard. Pending UL/CSA Certification)	120V/60Hz (USA & Canada Standard. CSA US & Canada Certified)
General Input	Wall Mounted: 288W (218W + 2x35W) Island Mounted: 358W (218W + 4x35W)	Wall Mounted: 200W (160W + 2x20W) Island Mounted: 240W (160W + 4x20W)
Motor Input Power	218 W	160 W
Motor Revolution	600 RPM ( $\pm 10\%$ ) to 1800 RPM ( $\pm 10\%$ )	800 RPM ( $\pm 10\%$ ) to 1300 RPM ( $\pm 10\%$ )
Levels Of Speed	6 Levels	3 Levels
Maximum Airflow	900 CFM	860 CFM
Air Pressure	320 pa Maximum	150 Pa (200 Pa Maximum)
Noise Level (dB / sone)	Approximately 20 / 0.5 to 56 / 7.1 (Lowest to highest Speed)	Approximately 30 / 0.75 to 60 / 7.0 (Lowest to Highest Speed)
Motor Type	Dual Chamber Ultra Quiet	Single Chamber Ultra Quiet
Fan Type	Dual Centrifugal / Sirocco	Centrifugal / Sirocco
Control Type	Dual Electronic Touch-Sensitive with LED Display (Both Sides)	Soft-Touch Push Button (Single Side)
Illumination	35W Dimmable Halogen	35W Halogen
Delayed Auto Shut Off	Programmable 1-15 minutes	Not Available
Cleaning Reminder	30 Hours	Not Available
Venting Size	6 inch Round	6 inch Round
Interference Protection	Radio Frequency Interference Protected	Radio Frequency Interference Protected